

NEW PRODUCT ANNOUNCEMENT


After 50 years leading as a windlass manufacturer.

The Time has come for **Lofrans'** to introduce **Chains for Anchoring!**



- ✓ **It is LOFRANS!!!**
- ✓ **Hot Dip Galvanized.**
- ✓ **Grade 40** - tougher than Grade 30 - over 30% higher breaking load.
- ✓ **Extended quality** tested on Lofrans' Windlasses
- ✓ **Lofrans' Authenticity Check** - "LFR" is engraved one in every 3 rings.

Code	72312	72313	72314	72315	72316	72317	72318
Type	ISO 4565 / DIN 766		DIN 766	ISO 4565		ISO 4565 / DIN 766	
A (mm)	6	8	10	10	12	14	16
B (mm)	18,5	24	28	30	36	41,5	45
C (mm)	20	27,5	34	34,5	39,6	47,4	54,6
D (mm)	8	11,5	14	14,5	15,6	19,4	22,6
E (mm)	30,5	40	48	50	60	69,5	77
Weight / m (kg)	0,8	1,42	2,2	2,28	3,23	4,37	5,72
Breaking load (kg)	2400	4300	6750	6750	9700	13230	17280
Pack (m)	100						



With the experience and quality of



Puntera de Proa



Puntera fija, INOX 304

Codigo	99638
Largo (mm)	165
Ancho (mm)	50
Diametro (mm)	64

BEST VALUE



Roldana para puntera 99638, negro

Codigo	11907
Largo (mm)	42
diam. (mm)	64
Material	PP & UV

BEST VALUE



Puntera basculante, Inox 316

Codigo	70634
Largo (mm)	328
Ancho (mm)	236
Grueso (mm)	70
Para cadena (mm)	6-8-10
Para ancla (kg)	hasta 14



Puntera bloqueante, Inox 316


Codigo	70612
Largo (mm)	240
Ancho (mm)	100
Para cadena (mm)	6-8
Para ancla (kg)	hasta 10

Cadena



Cadena calibrada galvanizada al fuego DIN 766, Bolsas

Code	71170	71171	71172	71173	71174	71175	71176	71177	71178	71179
A (mm)		6			8			10		12
B (mm)		18,5			24			30		36
C (mm)		20			27,5			34,5		39,6
D (mm)		8			11,5			14,5		15,6
E (mm)		30,5			40			50		60
Peso / m (kg)		0,8			1,42			2,28		3,23
Carga de Rotura (kg)		1632			3265			5102		7387
Bolsa (m)	10	30	50	10	30	50	10	30	50	50



Cadena Galvanizada al fuego, DIN5685A, Genovese

Codigo	72060	72061	72062	72063
A (mm)	5	7	10	13
B (mm)	21	28	40	52
C (mm)	20	28	40	52
D (mm)	10	14	20	26
E (mm)	31	42	60	78
Peso / m (kg)	775	1500	3100	5300
Carga de Rotura (kg)	0,5	1	2,05	3,45

NEW

Cadena Galvanizada al fuego, DIN 766, calibrada

Codigo	95617	95619	97710	97711
A (mm)	6	8	10	12
B (mm)	18.5	24	30	36
C (mm)	20	27.5	34.5	39.6
D (mm)	8	11.5	14.5	15.6
E (mm)	30.5	40	50	60
Peso / m (kg)	0.8	1.42	2.28	3.23
Carga de Rotura (kg)	1,632	3,265	5,102	7,387

Cadena, Inox 316, DIN 766, calibrada

Codigo	98042	98043	98044	98045	95637	97703
A (mm)	2	3	4	5	6	8
B (mm)	12	15		20	18.5	24
C (mm)	7.5	11	13	16	20	26
D (mm)	3.5	5	5	6	8	10
E (mm)	16	21	28	30	30.5	40
Peso / m (kg)	0.07	0.16	0.32	0.5	0.78	1.4
Carga de Rotura (kg)	127	408	816	1,275	1,632	3,265

Guarda cabos

Pre-cortado

BEST VALUE



Guarda cabos

Fabricados en nylon, son ligeros y resistentes. Disponibles en ocho tamaños para cabo de 8 a 22 mm

Código	95779	95780
Para cabo (mm)	20	22
Color	Blanco	
Packing(pzs)	1	

Cabos para uso general



Cabo
BY LALIZAS

Cabos para uso general

Fabricado en poliéster, blando, ideal para usos múltiples a bordo, desde amarrar anclas de capa hasta defensas.

NEW

Codigo	Diam. (mm)	Largo (m)	Carga de Rotura (kg)
92036	4	200	98
92037	5		146
92038	6		198
92039	8		320
92040	10		560
92041	12		760
92042	14	100	1020
92043	16		1460